according to 1907/2006/EC, Article 31



Printing date 19.02.2020

Version number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

- · Trade name: 4CR 0451-380 Hardener WP
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Sector of Use
- SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) • Product category PC9b Fillers, putties, plasters, modelling clay
- Application of the substance / the mixture Hardening agent/ Curing agent

\cdot 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: 4CR Vertriebsgesellschaft mbH Oberer Sommerfeldweg 2 D-94469 Deggendorf Tel.: +49 (0) 40 69 60 99 315 Fax: +49 (0) 40 69 60 99 316 E-Mail: Info@4CR.com www.4CR.com
1.4 Emergency telephone number: +49(0)700 24112112 (CRM)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008
- *The product is classified and labelled according to the CLP regulation. Hazard pictograms*
- · IIuzuru piciograms



· Signal word Danger

Hazard-determining components of labelling: acetone
Hazard statements
H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
Precautionary statements
P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.

(Contd. on page 2)

Revision: 19.02.2020

Printing date 19.02.2020

Version number 1

Trade name: 4CR 0451-380 Hardener WP

	(Contd. of page 1)
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	<i>TF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</i>
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional informa	ution:
EUH066 Repeated	exposure may cause skin dryness or cracking.
· 2.3 Other hazards	
· Results of PRT and	d vPvR assessment

esuus oj FBI ana vi vb assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol 🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319	50-100%	
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone	25-50%	
CAS: 7664-38-2 EINECS: 231-633-2 Reg.nr.: 01-2119485924-24	phosphoric acid Met. Corr.1, H290; Skin Corr. 1B, H314; () Acute Tox. 4, H302	<2.5%	
CAS: 75-65-0 EINECS: 200-889-7	2-methylpropan-2-ol Flam. Liq. 2, H225; () Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	<2.5%	
CAS: 558-30-5 EINECS: 209-193-8	2,2-dimethyloxirane Flam. Liq. 2, H225; Skin Corr. 1C, H314	≥0.1-<1%	
• Additional information: For the wording of the listed hazard phrases refer to section 16.			

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31

Printing date 19.02.2020

Version number 1



Trade name: 4CR 0451-380 Hardener WP

(Contd. of page 2)

• Information for doctor:

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
 Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
 7.2 Conditions for safe storage, including any incompatibilities
 Storage:
 Requirements to be met by storerooms and receptacles: Store in a cool location.
 Information about storage in one common storage facility: Store away from foodstuffs.
 - Further information about storage conditions: Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
 Storage class: 3
 - 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

according to 1907/2006/EC, Article 31



Printing date 19.02.2020

Version number 1

Trade name: 4CR 0451-380 Hardener WP

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

- 67-64-1 acetone
- WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

7664-38-2 phosphoric acid

WEL Short-term value: 2 mg/m³

Long-term value: 1 mg/m³

75-65-0 2-methylpropan-2-ol

WEL Short-term value: 462 mg/m³, 150 ppm Long-term value: 308 mg/m³, 100 ppm

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes. Avoid contact with the eyes and skin.
- · Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX

· Protection of hands:



Protective gloves (EN 374)

• Material of gloves Butyl rubber, BR

- Recommended thickness of the material: $\geq 0.7 \text{ mm}$
- · *Breakthrough time of glove material* Value for the permeation: Level ≤ 6
- · Eye protection:



Tightly sealed goggles

(Contd. on page 5)

GB

Safety data sheet according to 1907/2006/EC, Article 31



Printing date 19.02.2020

Version number 1

Trade name: 4CR 0451-380 Hardener WP

(Contd. of page 4)

• 9.1 Information on basic physical and c • General Information	nemicai properties
· Appearance:	
Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	:: 56 °C
· Flash point:	16 °C (DIN 53213)
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	425 °C (DIN 51794)
• Decomposition temperature:	Not determined.
• Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
· Explosion limits:	
Lower:	2.6 Vol %
Upper:	15 Vol %
· Vapour pressure at 20 °C:	233 hPa
· Density at 20 °C:	0.812 g/cm ³ (DIN 53217)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
\cdot Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	12 s (DIN 53211/4)
· Solvent content:	
Water:	2.5 %
VOC (EC)	<i>95.34 %</i>
Solids content (weight-%):	2.2 %
• 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 6)

according to 1907/2006/EC, Article 31



Version number 1



(Contd. of page 5)

Trade name: 4CR 0451-380 Hardener WP

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:					
64-17-5 ethanol					
Oral	LD50	7,060 mg/kg (rat)			
Dermal	LD50	<20,000 mg/kg (rabbit)			
Inhalative	LC50/4 h	20,000 mg/l (rat)			
		>8,000 mg/l (rabbit)			
Primary irritant effect:					

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) : slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

Safety data sheet according to 1907/2006/EC, Article 31



Printing date 19.02.2020

Version number 1

Trade name: 4CR 0451-380 Hardener WP

(Contd. of page 6)

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information	
14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR IMDG, IATA	UN1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	11
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number: Stowage Category	<i>F-E,<u>S-E</u> B</i>
14.7 Transport in bulk according to Annex II of	
	Not applicable.
Transport/Additional information:	
ADR	
Transport category	2
Tunnel restriction code	D/E
IMDG Limited quantities (LQ)	5L
UN ''Model Regulation'':	UN 1263 PAINT RELATED MATERIAL, 3, II

(Contd. on page 8)

according to 1907/2006/EC, Article 31



Printing date 19.02.2020

Version number 1

Trade name: 4CR 0451-380 Hardener WP

(Contd. of page 7)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

Class	Share in %
NK	50-100

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour. H290 May be corrosive to metals. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H341 Suspected of causing genetic defects. H351 Suspected of causing cancer. · Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids - Category 2 Met. Corr.1: Corrosive to metals - Category 1 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Corr. 1C: Skin corrosion/irritation - Category 1C Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Muta. 2: Germ cell mutagenicity – Category 2 Carc. 2: Carcinogenicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3