

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** 4CR 70-120 KH One-coat lacquer HB silk-mat/30
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
4CR Vertriebsgesellschaft mbH  
Oberer Sommerfeldweg 2  
D-94469 Deggendorf  
Tel.: +49 (0) 40 69 60 99 315  
Fax: +49 (0) 40 69 60 99 316  
E-Mail: [Info@4CR.com](mailto:Info@4CR.com)  
[www.4CR.com](http://www.4CR.com)
- **1.4 Emergency telephone number:** +49(0)700 24112112 (CRM)

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



GHS07

Skin Sens. 1      H317 May cause an allergic skin reaction.

STOT SE 3      H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**  
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics  
2-Methoxy-1-methylethyl acetate  
Hydrocarbons, C9, aromatics  
1-methoxy-2-propanol
- **Hazard statements**  
H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

**Trade name: 4CR 70-120 KH One-coat lacquer HB silk-mat/30**

(Contd. of page 1)

**Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read label before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

**2.3 Other hazards**
**Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**
**3.2 Chemical characterisation: Mixtures**

• **Description:** Mixture of substances listed below with nonhazardous additions.

**Dangerous components:**

EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	2.5-<10%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	<2.5%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; ⚠ Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; ⚠ Acute Tox. 4, H332; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319; ⚠ STOT SE 3, H335	1-<2.5%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	1-<2.5%
CAS: 7779-90-0 EINECS: 231-944-3 Reg.nr.: 01-2119485044-40	Trizinc bis(orthophosphate) ⚠ Aquatic Acute 1, H400; ⚠ Aquatic Chronic 1, H410	≥0.25-<2.5%
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	1-<2.5%
CAS: 96-29-7 EINECS: 202-496-6 Reg.nr.: 01-2119539477-28	2-butanone oxime ⚠ Carc. 2, H351; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H312; ⚠ Acute Tox. 4, H332; ⚠ Skin Sens. 1, H317	≥0.1-<1%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119524678-29	cobalt bis(2-ethylhexanoate) ⚠ Repr. 2, H361; ⚠ Aquatic Acute 1, H400; ⚠ Eye Irrit. 2, H319; ⚠ Skin Sens. 1A, H317; ⚠ Aquatic Chronic 3, H412	≥0.1-<0.25%

(Contd. on page 3)

**Trade name: 4CR 70-120 KH One-coat lacquer HB silk-mat/30**

CAS: 162627-17-0 EC number: 605-296-0 Reg.nr.: 01-2119970640-38	Fatty acids, C18-unsatd., dimers, reaction products with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine ----- ⚠ Skin Sens. 1A, H317	(Contd. of page 2) <0.1%
---	---	-----------------------------

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.
- **Information for doctor:**

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect from heat.  
Protect against electrostatic charges.

(Contd. on page 4)

**Trade name: 4CR 70-120 KH One-coat lacquer HB silk-mat/30**

(Contd. of page 3)

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
  - Requirements to be met by storerooms and receptacles: No special requirements.
  - Information about storage in one common storage facility: Store away from foodstuffs.
  - Further information about storage conditions:
    - Keep container tightly sealed.
    - Protect from heat and direct sunlight.
  - Storage class: 3
- 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

**108-65-6 2-Methoxy-1-methylethyl acetate**

WEL	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 274 mg/m <sup>3</sup> , 50 ppm
	Sk

**107-98-2 1-methoxy-2-propanol**

WEL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm
	Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
	Sk

**1330-20-7 Xylene**

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 220 mg/m <sup>3</sup> , 50 ppm
	Sk; BMGV

**123-86-4 n-Butyl acetate**

WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm
	Long-term value: 724 mg/m <sup>3</sup> , 150 ppm

**136-52-7 cobalt bis(2-ethylhexanoate)**

WEL	Long-term value: 0.1 mg/m <sup>3</sup>
	as Co; Carc, Sen

· **Ingredients with biological limit values:**

**1330-20-7 Xylene**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

- Additional information: The lists valid during the making were used as basis.

- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2 (EN 141, EN 143)

(Contd. on page 5)

**Trade name: 4CR 70-120 KH One-coat lacquer HB silk-mat/30**

(Contd. of page 4)

- **Protection of hands:**
- **Material of gloves**  
Fluorocarbon rubber (Viton)  
Recommended thickness of the material:  $\geq 0.7$  mm
- **Breakthrough time of glove material**  
For the mixture of chemicals the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).
- **Eye protection:**



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

### · 9.1 Information on basic physical and chemical properties

#### · General Information

##### · Appearance:

- |                  |                                    |
|------------------|------------------------------------|
| Form:            | Fluid                              |
| Colour:          | According to product specification |
| Odour:           | Characteristic                     |
| Odour threshold: | Not determined.                    |

· pH-value:	Not determined.
-------------	-----------------

#### · Change in condition

- |  |               |
|--|---------------|
| Melting point/freezing point:            | Undetermined. |
| Initial boiling point and boiling range: | 120.3 °C      |

· Flash point:	29 °C (DIN 53213)
----------------	-------------------

· Flammability (solid, gas):	Not applicable.
------------------------------	-----------------

· Ignition temperature:	>200 °C (DIN 51794)
-------------------------	---------------------

· Decomposition temperature:	Not determined.
------------------------------	-----------------

· Auto-ignition temperature:	Product is not selfigniting.
------------------------------	------------------------------

· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
-------------------------	---

#### · Explosion limits:

- |        |           |
|--------|-----------|
| Lower: | 0.6 Vol % |
| Upper: | 8 Vol %   |

· Vapour pressure:	Not determined.
--------------------	-----------------

· Density at 20 °C:	1.221 g/cm <sup>3</sup> (DIN 53217)
---------------------	-------------------------------------

· Relative density	Not determined.
--------------------	-----------------

· Vapour density	Not determined.
------------------	-----------------

· Evaporation rate	Not determined.
--------------------	-----------------

#### · Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water:	Not determined.
---	-----------------

#### · Viscosity:

- |                     |                     |
|---------------------|---------------------|
| Dynamic:            | Not determined.     |
| Kinematic at 20 °C: | 290 s (DIN 53211/4) |

(Contd. on page 6)

**Trade name: 4CR 70-120 KH One-coat lacquer HB silk-mat/30**

(Contd. of page 5)

· **Solvent content:**

**Water:** 0.0 %  
**VOC (EC)** 35.30 %

**Solids content (weight-%):** 64.7 %

· **9.2 Other information** No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

**64742-95-6 Hydrocarbons, C9, aromatics**

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

**7779-90-0 Trizinc bis(orthophosphate)**

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

**96-29-7 2-butanone oxime**

Oral	LD50	3,700 mg/kg (rat)
Dermal	LD50	1,100 mg/kg (rat)
Inhalative	LC50/4 h	20 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.

(Contd. on page 7)

**Trade name: 4CR 70-120 KH One-coat lacquer HB silk-mat/30**

(Contd. of page 6)

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (German Regulation) : hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
-----------	---

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |                                       |              |
|---------------------------------------|--------------|
| · <b>14.1 UN-Number</b>               | UN1263       |
| · <b>ADR, IMDG, IATA</b>              |              |
| · <b>14.2 UN proper shipping name</b> |              |
| · <b>ADR</b>                          | UN1263 PAINT |
| · <b>IMDG, IATA</b>                   | PAINT        |

#### · **14.3 Transport hazard class(es)**

##### · **ADR**



- |                |                           |
|----------------|---------------------------|
| · <b>Class</b> | 3 (F1) Flammable liquids. |
| · <b>Label</b> | 3                         |

##### · **IMDG, IATA**



- |                |                      |
|----------------|----------------------|
| · <b>Class</b> | 3 Flammable liquids. |
| · <b>Label</b> | 3                    |

(Contd. on page 8)



**Trade name: 4CR 70-120 KH One-coat lacquer HB silk-mat/30**

(Contd. of page 7)

· <b>14.4 Packing group</b>	
· <b>ADR, IMDG, IATA</b>	III
· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
· <b>Danger code (Kemler):</b>	30
· <b>EMS Number:</b>	F-E, <u>S-E</u>
· <b>Stowage Category</b>	A
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	D/E
· <b>Remarks:</b>	≤ 450 l: 2.2.3.1.5 ADR
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Remarks:</b>	≤ 5 l: 2.2.3.1.5 IMDG
· <b>UN "Model Regulation":</b>	UN 1263 PAINT, 3, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c** FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **National regulations:**

Class	Share in %
I	<1
NK	25-50

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.

(Contd. on page 9)



**Trade name: 4CR 70-120 KH One-coat lacquer HB silk-mat/30**

(Contd. of page 8)

H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

• **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

• **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Dam. 1: Serious eye damage/eye irritation – Category 1  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1  
Skin Sens. 1A: Skin sensitisation – Category 1A  
Carc. 2: Carcinogenicity – Category 2  
Repr. 2: Reproductive toxicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3