

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** 4CR 72-148 AC 2K Topcoat High resistance glossy/90
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Paint
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
4CR Vertriebsgesellschaft mbH
Oberer Sommerfeldweg 2
D-94469 Deggendorf
Tel.: +49 (0) 40 69 60 99 315
Fax: +49 (0) 40 69 60 99 316
E-Mail: Info@4CR.com
www.4CR.com
- **1.4 Emergency telephone number:** +49(0)700 24112112 (CRM)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02



GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**
n-Butyl acetate
2-Methoxy-1-methylethyl acetate
Hydrocarbons, C9, aromatics
- **Hazard statements**
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

(Contd. on page 2)

Trade name: 4CR 72-148 AC 2K Topcoat High resistance glossy/90

(Contd. of page 1)

- P103 Read label before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains 2,3-epoxypropyl neodecanoate. May produce an allergic reaction.
 - **2.3 Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-Methoxy-1-methylethyl acetate Flam. Liq. 3, H226; STOT SE 3, H336	2.5-<10%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-<5%
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-Butoxyethyl acetate Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	2.5-<5%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Aquatic Chronic 3, H412	<2.5%
CAS: 26761-45-5 EINECS: 247-979-2 Reg.nr.: 01-2119431597-33	2,3-epoxypropyl neodecanoate Muta. 2, H341; Aquatic Chronic 2, H411; Skin Sens. 1, H317	≥0.25-<1%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

Trade name: 4CR 72-148 AC 2K Topcoat High resistance glossy/90

(Contd. of page 2)

- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.
- **Information for doctor:**

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 3
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

Trade name: 4CR 72-148 AC 2K Topcoat High resistance glossy/90

(Contd. of page 3)

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-Butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

108-65-6 2-Methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
-----	--

1330-20-7 Xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

112-07-2 2-Butoxyethyl acetate

WEL	Short-term value: 332 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Sk
-----	---

100-41-4 ethylbenzene

WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
-----	---

· **Ingredients with biological limit values:**

1330-20-7 Xylene

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A/P2 (EN 141, EN 143)

· **Protection of hands:**



Protective gloves (EN 374)

· **Material of gloves**

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

· **Breakthrough time of glove material** Value for the permeation: Level ≤ 3

(Contd. on page 5)

Trade name: 4CR 72-148 AC 2K Topcoat High resistance glossy/90

(Contd. of page 4)

· **Eye protection:**

Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· Form:	Fluid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	124 °C

· **Flash point:** 30 °C (DIN 53213)· **Flammability (solid, gas):** Not applicable.· **Ignition temperature:** 315 °C (DIN 51794)· **Decomposition temperature:** Not determined.· **Auto-ignition temperature:** Product is not selfigniting.· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.· **Explosion limits:**

· Lower:	1.2 Vol %
· Upper:	7.5 Vol %

· **Vapour pressure at 20 °C:** 10.7 hPa· **Density at 20 °C:** 1.09 g/cm³ (DIN 53217)· **Relative density** Not determined.· **Vapour density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.· **Viscosity:**

· Dynamic:	Not determined.
· Kinematic at 20 °C:	140 s (DIN 53211/4)

· **Solvent content:**· **VOC (EC)** 42.87 %· **Solids content (weight-%):** 57.1 %· **9.2 Other information** No further relevant information available.

Trade name: 4CR 72-148 AC 2K Topcoat High resistance glossy/90

(Contd. of page 5)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

64742-95-6 Hydrocarbons, C9, aromatics

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) : slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 7)

Trade name: 4CR 72-148 AC 2K Topcoat High resistance glossy/90

(Contd. of page 6)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
-----------	---

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN-Number**

· **ADR, IMDG, IATA** UN1263

· **14.2 UN proper shipping name**

· **ADR** UN1263 PAINT
· **IMDG, IATA** PAINT

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class** 3 (F1) Flammable liquids.
· **Label** 3

· **IMDG, IATA**



· **Class** 3 Flammable liquids.
· **Label** 3

· **14.4 Packing group**

· **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**

· **Marine pollutant:** No

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Danger code (Kemler):** 30

· **EMS Number:** F-E,S-E

· **Stowage Category** A

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Transport category** 3

· **Tunnel restriction code** D/E

(Contd. on page 8)

Trade name: 4CR 72-148 AC 2K Topcoat High resistance glossy/90

(Contd. of page 7)

· Remarks:	≤ 450 l: 2.2.3.1.5 ADR
· IMDG	
· Limited quantities (LQ)	5L
· Remarks:	≤ 5 l: 2.2.3.1.5 IMDG
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

· **National regulations:**

Class	Share in %
NK	25-50

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· **Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 9)

**Trade name: 4CR 72-148 AC 2K Topcoat High resistance glossy/90**

(Contd. of page 8)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Muta. 2: Germ cell mutagenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB